



- Flush Mount Square 2-ring LED Ceiling Fixture
- Die-formed cold-rolled steel housing with high transmission acrylic diffuser create excellent light distribution and uniformity
- High efficiency 2835 LED module, up to 100lm/W
- Triac Dimming, 5-100% dim range
- High Power Factor, Low THD
- Suitable for damp location
- 50,000H @ L70 Long Lifetime




SPECIFICATION

PART #	INPUT (Vac)	OUTPUT (W)	DELIVERED LUMEN OUTPUT (LM)	EFFICACY (LPW)	CRI	AVAILABLE CCT (K)	DIMMING	FINISH	DIMENSION
FMS2-1215	120	15	1050	70	80/90	3000/4000/5000/3CCT Selectable	Triac / 0-10V	NICKEL&BRO NZE	16 Inch Dia.
FMS2-1220	120	20	1400	70	80/90	3000/4000/5000/3CCT Selectable	Triac / 0-10V	NICKEL&BRO NZE	16 Inch Dia.
FMS2-1415	120	15	1050	70	80/90	3000/4000/5000/3CCT Selectable	Triac / 0-10V	NICKEL&BRO NZE	16 Inch Dia.
FMS2-1420	120	20	1400	70	80/90	3000/4000/5000/3CCT Selectable	Triac / 0-10V	NICKEL&BRO NZE	24 Inch Dia.

DIMENSION

Size (Inch)	FMS2-12	FMS2-14
L	12	14
W	12	14
H	3-1/4"	3-1/4"



PACKAGING

PART#	INDIVIDUAL BOX	UNITS/MASTER	MASTER BOX	WEIGHT	UNITS/40'HQ FCL	VOLUMN	WEIGHT
FMS2-1215	325x325x90mm	4	345x345x387mm		2552	65 CBM	
FMS2-1220	325x325x90mm	4	345x345x387mm		2552	65 CBM	
FMS2-1415	376x376x90mm	4	396x396x387mm		2552	65 CBM	
FMS2-1420	376x376x90mm	4	396x396x387mm		1408	65 CBM	