



- ECO Retrofit Recessed Round LED Down Light
- 120V Line Voltage, Driver-On-Board Solution
- Triac dimming, 5-100% dim range
- 5 CCT Selectable
- High CRI >90
- Beam angle 100°
- For Retrofit quick installation
- 50,000H @L70 long lifetime
- 5 years Warranty




ORDERING GUIDE


PART #	SIZE	INPUT (Vac)	OUTPUT (W)	LUMEN OUTPUT (LM)	CRI	CCT (K) SELECTABLE	CONTROL	FINISH	CERTIFICATION
RDER5C-410-LBTR	4"	120	10	700	90	2700/3000/3500/4000/5000	Triac Dimming	WHITE	ETL, ES, JA8
RDER5C-615-LBTR	6"	120	15	1050	90	2700/3000/3500/4000/5000	Triac Dimming	WHITE	ETL, ES, JA8

KEY FEATURES

LUMINAIRE PHOTOMETRIC



5-level slider switch - 5 CCT selectable



IESNA	LM-63-2002
Light source	LED
Output Watts	50
CCT	5000K
Total Lumens	5000
Efficiency	100 LPW
Beam Angle	114.9°

Replaceable Trim Options:

- Brush Nickel
- Bronze
- Black




Accessories:

- E26 Adapter



DIMENSION

Size (mm)	4"	6"
A	130	184
B	69	79
C	25	20



PACKAGING

PART#	INNER BOX	UNIT / BOX	MASTER BOX	WEIGHT	UNITS/40'HQ FCL	VOLUMN	WEIGHT
RDER5C-410	140x140x7.5mm	12	440x290x160mm	2.95KG	37000	65CBM	9110 KG
RDER5C-615	240x240x12.5mm	4	480x260x275mm	2.9 KG	7600	65CBM	5510 KG