



- Stylish and compact cylinder design with integrated LED driver.
- Die-cast aluminum housing optimizes thermal management
- Modular features comply with different optical accessories for custom lighting applications.
- Proprietary joint allows 360° horizontal rotation adjustment and 90° vertical aiming.
- 120Vac, 0-10V dimming standard
- Complies with UL1598 and CSA C22.2
- 50,000H @L70 long lifetime




## ORDERING GUIDE

PART #	INPUT (Vac)	OUTPUT (W)	LUMEN OUTPUT (LM)	EFFICACY	CRI	AVAILABLE CCT (K)	DIMMING	FINISH	CERTIFICATION
THPC-103P/4P	120	10	1000-1100	110	80/90	2700/3000/4000	0-10V	BRONZE	ETL, DLC
THPC-203P/4P	120	20	2250-2520	110	80/90	2700/3000/4000	0-10V	BRONZE	ETL, DLC
THPC-25-3P/4P	120	25	2600-2850	110	80/90	2700/3000/4000	0-10V	BRONZE	ETL, DLC
THPC-30-3P/4P	120	30	3100-3350	110	80/90	2700/3000/4000	0-10V	BRONZE	ETL, DLC

## KEY FEATURES

## LUMINAIRE PHOTOMETRIC


### Optical Accessories Optional:




IESNA	LM-63-2002
Light source	COB LED
Input Watts	30
CCT	4000K
Total Lumens	3246.2
Efficiency	108 LPW
Beam Angle	55.7

## DIMENSION

Size (mm)	THPC30-3P	THPC30-4P
A	Φ84	Φ84
B	150	150
C	172	172
D	220	215



3P Single Circuit Track Head



4P Three Circuit Track Head



3P Track



4P Track

## PACKAGING

PART#	UNIT / BOX	MASTER BOX	WEIGHT	UNITS/40'HQ FCL	VOLUMN	WEIGHT
THP-10	18	580 x 380 x 300 mm	17.50 KG	18,180	66 CBM	74,675 KG
THP-20	15	580 x 380 x 300 mm	16.05KG	15,450	68 CBM	16,530 KG
THP-30	15	580 x 380 x 300 mm	16.95KG	15,450	68 CBM	17,450 KG