



- Robust die-cast aluminum housing
- High impact, heat resistant borosilicate glass lens
- Low-wattage consumption with highly efficient LEDs Engine
- 120V Line Voltage, Driver-On-Board Solution
- Available for Wall Mount or Ceiling Mount
- Suitable for wet location
- 50,000H @L70 long lifetime





### SPECIFICATION

PART #	INPUT (Vac)	OUTPUT (W)	DELIVERED LUMEN OUTPUT (LM)	EFFICACY (LPW)	CRI	AVAILABLE CCT (K)	DIMMING	FINISH	DIMENSION
WBK3-06	120	6	420	70	80	3000/4000/5000	Triac Dim.	Bronze/Black	10-3/8"Lx10-3/8"Wx 5-1/8"D
WBK3-09	120	9	630	70	80	3000/4000/5000	Triac Dim.	Bronze/Black	10-3/8"Lx10-3/8"Wx 5-1/8"D
WBK3-15	120	15	1050	70	80	3000/4000/5000	Triac Dim.	Bronze/Black	10-3/8"Lx10-3/8"Wx 5-1/8"D

### DIMENSION

Size (Inch)	WBK3
L	10-3/8"
W	10-3/8"
D	5-1/8"



### PACKAGING

PART#	INDIVIDUAL BOX	UNITS/MASTER	MASTER BOX	WEIGHT	UNITS/40'HQ FCL	VOLUMN	WEIGHT
WBK3-06	269x152x270mm	4	556x322x290mm		4931	65 CBM	
WBK3-09	269x152x270mm	4	556x322x290mm		4931	65 CBM	
WBK3-15	269x152x270mm	4	556x322x290mm		4931	65 CBM	