



- Robust die-cast aluminum housing, elegant slim design Mini Slim Wall Pack
- High Transmission Glass Diffuser - White or Frosted optional
- Low-watt consumption with high-efficient LEDs
- 120V Line Voltage, Driver-On-Board Solution
- IP65 Suitable for wet location
- 50,000H @L70 long lifetime




SPECIFICATION

| PART # | INPUT (Vac) | OUTPUT (W) | DELIVERED LUMEN OUTPUT (LM) | EFFICACY (LPW) | CRI | AVAILABLE CCT (K) | DIMMING | FINISH | DIMENSION |
|-----------|-------------|------------|-----------------------------|----------------|-----|---------------------|------------|--------------|----------------------|
| WMD5-1009 | 120 | 9 | 630 | 70 | 80 | 3000/4000/5000/3CCT | Triac Dim. | Bronze/Black | 10"Hx7-1/8"Wx3-3/4"D |
| WMD5-1812 | 120 | 12 | 840 | 70 | 80 | 3000/4000/5000/3CCT | Triac Dim. | Bronze/Black | 18"Lx7-7/8"Wx3-3/4"E |
| WMD5-2415 | 120 | 15 | 1050 | 70 | 80 | 3000/4000/5000/3CCT | Triac Dim. | Bronze/Black | 24"Lx7-7/8"Wx3-3/4"E |

DIMENSION

| Size (Inch) | WMD5-12 | WMD5-18 | WMD5-24 |
|-------------|---------|---------|---------|
| H | 10" | 18" | 24" |
| W | 7-1/8" | 7-1/8" | 7-1/8" |
| D | 3-3/4" | 3-3/4" | 3-3/4" |



PACKAGING

| PART# | INDIVIDUAL BOX | UNITS/MASTER | MASTER BOX | WEIGHT | UNITS/40'HQ FCL | VOLUMN | WEIGHT |
|-----------|----------------|--------------|---------------|--------|-----------------|--------|--------|
| WMD5-1009 | 220x115x318mm | 6 | 457x367x338mm | | 6774 | 65 CBM | |
| WMD5-1812 | 220x115x318mm | 6 | 457x367x338mm | | 6774 | 65 CBM | |
| WMD5-2415 | 220x115x318mm | 6 | 457x367x338mm | | 6774 | 65 CBM | |