



- Robust die-cast aluminum housing, elegant slim design Mini Slim Wall Pack
- High Transmission Glass Diffuser - White or Frosted optional
- Low-watt consumption with high-efficient LEDs
- 120V Line Voltage, Driver-On-Board Solution
- IP65 Suitable for wet location
- 50,000H @L70 long lifetime



SPECIFICATION

PART #	INPUT (Vac)	OUTPUT (W)	DELIVERED LUMEN OUTPUT (LM)	EFFICACY (LPW)	CRI	AVAILABLE CCT (K)	DIMMING	FINISH	DIMENSION
WPM2-06	120	6	420	70	80	3000/4000/5000	Triac Dim.	Bronze/Black	9-7/8"Lx6-1/4"Wx3-1/2"E
WPM2-09	120	9	630	70	80	3000/4000/5000	Triac Dim.	Bronze/Black	9-7/8"Lx6-1/4"Wx3-1/2"E
WPM2-12	120	12	840	70	80	3000/4000/5000	Triac Dim.	Bronze/Black	9-7/8"Lx6-1/4"Wx3-1/2"E

PACKAGING

PART#	INDIVIDUAL BOX	UNITS/MASTER	MASTER BOX	WEIGHT	UNITS/40'HQ FCL	VOLUMN	WEIGHT
WPM2-06	188x115x280mm	6	395x370x300mm		8758	65 CBM	
WPM2-09	188x115x280mm	6	395x370x300mm		8758	65 CBM	
WPM2-12	188x115x280mm	6	395x370x300mm		8758	65 CBM	