



- Robust die-cast aluminum housing, elegant slim design Mini Slim Wall Pack
- High Transmission Glass Diffuser - White or Frosted optional
- Low-watt consumption with high-efficient LEDs
- 120V Line Voltage, Driver-On-Board Solution
- IP65 Suitable for wet location
- 50,000H @L70 long lifetime



SPECIFICATION

PART #	INPUT (Vac)	OUTPUT (W)	DELIVERED LUMEN OUTPUT (LM)	EFFICACY (LPW)	CRI	AVAILABLE CCT (K)	DIMMING	FINISH	DIMENSION
WPM5-09	120	9	600	70	80	3000/4000/5000	Triac Dim.	Bronze/Black	9-3/4"Lx7-1/8"Wx3-3/4"E
WPM5-12	120	12	900	70	80	3000/4000/5000	Triac Dim.	Bronze/Black	9-3/4"Lx7-1/8"Wx3-3/4"E
WPM5-15	120	15	1200	70	80	3000/4000/5000	Triac Dim.	Bronze/Black	9-3/4"Lx7-1/8"Wx3-3/4"E

PACKAGING

PART#	INDIVIDUAL BOX	UNITS/MASTER	MASTER BOX	WEIGHT	UNITS/40'HQ FCL	VOLUMN	WEIGHT
WPM5-09	200x128x277mm	6	417x407x297mm		7618	65 CBM	
WPM5-12	200x128x277mm	6	417x407x297mm		7618	65 CBM	
WPM5-15	200x128x277mm	6	417x407x297mm		7618	65 CBM	