



- **Patented** Thin and tidy design with portable handle ring, contains **8.2ft (2.5m)** cord wrapped around
- Robust foldable and mountable bracket, **185°** adjustable
- **8000mAh** Built-in Emergency Battery Pack, Lasts **15hrs** @10% brightness of 300lm.
- 3-level Rocker Switch: Off/**10%/100%** selectable brightness.
- **100lm/W** High brightness.
- **IK07** Protection Rated Robust Housing.
- **IP65** Suitable for damp location.
- Lamp lifespan more than **50,000** hours.



ORDERING GUIDE

PART #	INPUT (VAC)	OUTPUT (W)	LUMEN OUTPUT (LM)	EFFICACY (LPW)	CRI	AVAILABLE CCT (K)	CONTROL	FINISH	VERSION
PWL-JB50	120	50W @120Vac 25W @Battery	6000 @120V 2500lm @Battery	100	>80	4000/5000/6000	10%/100% Brightness Selectable	Amber & Black	Battery Backup

KEY FEATURES

Housing

Aluminum Heat Sink + Robust and High Tenacity PC+ABS Handle Ring, 180° Adjustable and Mountable Bracket.



Optical

120° Beam Angle LED + High Transmittance Tempered Glass.



Electrical

LED Driver: 120V input


3-level Rocker Switch: OFF/10%/100% Brightness Selectable.



Lithium Battery backup: 8000mAh, lasts 1.5 hours @ 100% brightness of 25W 2500lm, or 12 hours @10% brightness of 2.5W 250lm.




LUMINAIRE PHOTOMETRIC



IESNA	LM-63-2002
Light source	LED
Output Watts	50
CCT	5000K
Total Lumens	5000
Efficiency	100 LPW
Beam Angle	114.9°

DIMENSION

Size (mm)	PWL-JB50
W	226
H	313
D	55



PACKAGING

PART#	INNER BOX	UNIT / BOX	MASTER BOX	WEIGHT	UNITS/40'HQ FCL	VOLUMN	WEIGHT
PWL-JB50	330x245x75 mm	10	510x405x350 mm	20.5 KG	9000	65CBM	18450 KG