



- Robust die-cast aluminum housing
- High impact, heat resistant borosilicate glass lens
- Low-wattage consumption with highly efficient LEDs Engine, up to 100lm/W
- 120V Line Voltage, Driver-On-Board Solution
- Available for Wall Mount only
- Suitable for wet location
- 50,000H @L70 long lifetime



**SPECIFICATION**

PART #	INPUT (Vac)	OUTPUT (W)	DELIVERED LUMEN OUTPUT (LM)	EFFICACY (LPW)	CRI	AVAILABLE CCT (K)	DIMMING	FINISH	DIMENSION
WML1-06	120	6	420	70	80	3000/4000/5000	Triac Dim.	Bronze/Black	11-1/2"Hx10"Wx 4-3/4"D
WML1-09	120	9	630	70	80	3000/4000/5000	Triac Dim.	Bronze/Black	11-1/2"Hx10"Wx 4-3/4"D
WML1-12	120	12	840	70	80	3000/4000/5000	Triac Dim.	Bronze/Black	11-1/2"Hx10"Wx 4-3/4"D

**DIMENSION**

Size (Inch)	WML1
H	11-1/2"
W	10"
D	4-3/4"

**PACKAGING**

PART#	INDIVIDUAL BOX	UNITS/MASTER	MASTER BOX	WEIGHT	UNITS/40'HQ.FCL	VOLUMN	WEIGHT
WML1-06	342x304x171	6	628x533x362mm		3,169	65 CBM	
WML1-09	342x304x171	6	628x533x362mm		3,169	65 CBM	
WML1-12	342x304x171	6	628x533x362mm		3,169	65 CBM	